

AQUEOUS PMB700--PP MATTE PAPER 160

PP matte paper160 is an asymmetrically coated, matte polypropylene film with curl-free and high opacity blockout film that express brilliant color reproduction. It has application for promotional roll-up, posters, points of sales, trade show graphics.

The matte film has a water resistant coating and a Ultra white surface.

This product requires three main things to be a professional banner: the great color representation, anti-curl and reducing light or reflections on the printed surface. These feature

APPLICATION

posters, point of sales, point of purchase displays, trade show panels, graphics, instruction plates, indoor/outdoor promotional banners, retail aisle banners

SPECIFICATION

| Caliper |
|---------------|
| weight |
| Base material |
| Surface |
| |

153 micron (6.1 mil) 100g PP Matte

Width Length Core 36", 50", 60" 30m (100 ft) 2"

TECHNICAL DATA

| Caliper | 153 micron | ASTM D645 |
|---------|-----------------------|-----------------|
| Caliper | 155 11101011 | ASTIVI D045 |
| Gloss | 60° : 3.0 / 85° : 5.0 | ASTM D2457 |
| L.a.b | 85 / 2.0 / -9.0 | ANSI T |
| | | (D50/2º/Abs/No) |

Printer Compatibility

COMPATIBILITY

Ink Compatibility

Dve

(\bigstar Excellent, \bigcirc Very good, \bigcirc Good, \triangle Fair, X Not good)

Pigment

Most Aqueous Printing system, Especially New Printers HP Z-Series, Canon IPF Series, Epson, Rolan Mimaki, Mutoh

New

| GUIDELINES | |
|--------------|---|
| Printing Tip | Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60% Use care in handling printed material, surface susceptible to abrasion To optimize the printing quality, printer need to be set for hightest print quality. |
| Lamination: | Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminate is recommended. |
| Storage: | It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH |
| Shelf Life: | One year stored in original package in recommended condition |

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affact results.



Head office (Korea) **Natura Media Inc.** Tel : +82-(0)2-3788-0365 Fax : +82-(0)2-3788-0326 sales@naturamedia.co.kr Europe Branch (Belgium) Natura Europe S.A Tel : +32-65-225-509 Fax : +32-65-554-174 jh.hong@naturamedia.co.kr USA Carson Office **Natura Media USA Inc.** Tel : +1-310-549-5590 Fax : +1-310-513-9826 hmshin@naturamedia.co.kr