

SOLVENT

SO490--

SOLVENT SMOOTH ROLL UP BANNER MATTE

1. 99.9% Block-out : Middle/Back double treated
2. Multi-layered by Double PP : enforced heat Resistant and Flatness

SOLVENT SMOOTH ROLL UP BANNER MATTE is matte, Polypropylene banner applicable for indoor and outdoor. Also it's high opacity blockout film that expresses brilliant color reproduction. It has high image quality along with durability, tear-resistancy, eco-friendly. Additionally, the high cost effectiveness compared to PET based roll up will be great solution for you. It has application for promotional roll-up, posters, points of sales, trade show graphics.

APPLICATION

Roll-up banner, X,Y Banners
 Point of purchase, point of purchase displays
 Posters, trade show
 High resolution graphics


SPECIFICATION

Caliper	195 micron (7.8 mil)
weight	160g
Base material	PP Multi-layered
Surface	Semi-Matte
Width	36", 50", 60"
Length	30m (100 ft)
Core	3"

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility



Printer Compatibility

Most Solvent & Eco Solvent Printing system: LATEX & HP, Epson, Roland, Mimaki, Mutoh, Seiko, Oce

TECHNICAL DATA

Caliper	205 micron	ASTM D645
Gloss	60° : 15.0 / 85° : 30.0	ASTM D2457
L.a.b	90.0 / 0 / -5.0	ANSI T (D50/2°/Abs/No)

GUIDELINES

Printing Tip

Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%
 Use care in handling printed material, surface susceptible to abrasion
 To optimize the printing quality, printer need to be set for highest print quality.

Lamination:

Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended.

Storage:

It is recommended to store in the closed original packing in a cool and dry environment
 Temperature 10~25°C (50~77°F), Relative Humidity 50% RH

Shelf Life:

One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.